Appln. No. 10/830,070 Amd. dated June 6, 2005 Reply to Office Action of March 9, 2005

## Amendments to the Abstract

Please replace the Abstract with the following amended Abstract of the Disclosure:

## Abstract of the Disclosure

There is provided a A die 1, for molding disc substrates, whereinincludes, in a stamper20, a to-be-held surface 33 that diverges continuously from an inner circumferential surface-32 of a center hole. 31 is formed between the inner circumferential surface 32 and an inner circumferential side head surface 34 by punching the center hole 31, an An inner stamper holder 16 that holds holding the inner circumferential side 20a of the stamper 20-includes a cylindrical body portion 41 and a claw portion 42, in the claw portion, including a cavity forming surface 43 that is substantially parallel to the inner circumferential side head surface-34-of-the stamper 20, and a holding surface 46 that diverges diverging tapered toward the cavity in a tapered fashion and holds said holding the to-beheld surface. 33 are formed, and, in the cylindrical body portion 41, a cylindrical surface 47-that is opposed to the inner

- 4 -

Appln. No. 10/830,070 Amd. dated June 6, 2005 Reply to Office Action of March 9, 2005

circumferential surface 32—of the stamper—20—is

formed. The die 1—for molding—the dise

substrates—prevents the claw portion 42—of the

inner stamper holder 16—from—being projected

projecting from a transfer surface 35—of the

stamper 20—and solves a problem of insufficient

strength of the inner circumferential side of the

stamper—20.

- 5 -